

DECOFIT® P



Technische Eigenschaften

Basis	Synthetic dispersion
Consistency	Paste
Curing system	Physical drying
Open time (*)	Approximately 15 to 20 Minuten
Drying time (*)	Approximately 24 hours
Density (DIN 53479)	Approximately 1,60 g/ml
Temperature resistance	-20°C tot +70°C (after hardening)
Consumption	250 – 650 g/m ²

(*) These values can variate according to ambient conditions such as temperature, humidity, substrate

Product description

DECOFIT® P is a ready to use adhesive for bonding decorative panels onto surfaces indoor.



NMC sa
Gert-Noël-Strasse – B-4731 Eynatten
☎ +32 87 85 85 00 – 📠 +32 87 85 85 11
info@nmc.eu

www.nmc.eu



DECOFIT[®] P



Properties

- Ready to use
- Strong adhesive power
- Solvent free
- Suitable for sanding
- Suitable for painting

Applications

Bonding of decorative mouldings, ceiling tiles and centres.

Packaging

- Colour: White
- Packaging size: Tube 400 gr
Cartridge 310ml
Bucket 1-4-5-7 kg

Shelf life

At least 18 months in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25°C.

Substrate

Nature: All usual porous building materials such as brick, concrete, plaster, wood.

Condition: clean, dry and free from dust and grease.

Pre-treatment: A primer is recommended for very porous substrates.

We recommend a preliminary compatibility test.

DECOFIT® P

Application method

Method:

For wall insulation: Apply the adhesive on the wall, using a toothed 2,50mm spatula. Apply the undercoat to the wall and press down gently. Use a wallpaper paste knife or brush to ensure good adhesion.

For ceiling tiles and panelling: Apply 5 to 9 knobs of adhesive on the back of the tile or on the edge of the panelling. Place the tile on the ceiling by pressing gently.

Application temperature: +5°C to 35°C

Clean: Uncured Decofit® P may be removed from tools and materials with water. Cured adhesive must be removed mechanically.

Repair: with DECOFIT® P

Health,- and Safety recommendations

Take the usual labour hygiene into account.
Consult the packaging label for more information.

